



DX Magnetizing Power

The table of model							
Model	DX-10100-15	DX-10200-15	DX-1520-30	DX-2510-30	DX-2520-30	DX-2530-30	DX-2540-30
Input Power	AC220V 50~60Hz 30A			AC220V 50~60Hz 40A			
Max Output Current	15,000		30,000	30,000			
Charge Voltage	DC50~1000V		DC50~1500V	DC50~2500V			
Repeat Precision of Charge Voltage	±1V+1digit		±1V+1digit	±1V+1digit			
Charge Time	5 (sec)	9 (sec)	5 (sec)	4 (sec)	5 (sec)	8 (sec)	10 (sec)
The Capacity of Condenser	10,000uF	20,000uF	2,000uF	1,000uF	2,000uF	3,000uF	4,000uF
The Capacity Changing	5,000/10,000	10,000/20,000	1000/2000	No	1,000/2,000	1,000/2,000/3,000	1,000/2,000/4,000
Main Switch	SCR		SCR	SCR			
Discharge Ampere Meter (Compare Function)	Have		Have	Have			
Interior Discharge Circuit	Have		Have	Have			
Enclosure Dimensions	600W×900D×1350H			600W×900D×1350H	700W×1180D×1450H		
Weight	200Kg	300Kg	250Kg	300Kg	400Kg	500Kg	600Kg

Add: No.86-101,RD West Jinshan, Huli Dist, Xiamen, China Zip code: 361009

Tel: 86-592-5237772

Fax: 86-592-5237901

Email:sales@magnetsource.com.cn, dexing2007@gmail.com

Home page:<http://www.magnetsource.com.cn> <http://www.magnetomachinery.com> <http://www.rubber-magnet.com>