



Dexing Magnet Tech. Co., Ltd

The Special Magnetizing Power

The table of model						
Model	DX-1504-10	DX-1506-10	DX-1510-30 II	DX-1520-30 II V	DX-2510-30 II	DX-4030-30 II
Input Power	AC220V 50~60Hz 10A		AC220V 50~60Hz 15A	AC220V50~60Hz 30A	AC220V50~60Hz 40A	AC220V 50~60Hz 60A
Max Output Current	10,000	10,000	30,000×2	30,000×2	30,000×2	30000×2
Charge Voltage	DC50~1500V		DC50~1500V	DC50~1500V	DC50~2500V	DC200~4000V
Repeat Precision of Charge Voltage	±1V+1digit		±1V+1digit	±1V+1digit		
Charge Time	2 (sec)		4 (sec)	5 (sec)	4 (sec)	12 (sec)
The Capacity of Condenser	400uF	600uF	1,000uF	2,000uF	1,000uF	3,000uF
The Capacity Changing	Haven' t	400/600	Haven' t	1,000/2,000	Haven' t	1,000/2,000/3,000
Main Switch	SCR		SCR	SCR		
Discharge Ampere Meter (Compare Function)	Have		Have	Have		
Interior Discharge Circuit	Have		Have	Have		

Add: No.86-101,RD West Jinshan, Huli Dist, Xiamen, China Zip code: 361009

Tel: 86-592-5237772

Fax: 86-592-5237901

Email:sales@magnetsource.com.cn, dexing2007@gmail.com

Home page:<http://www.magnetsource.com.cn> <http://www.magnetomachinery.com> <http://www.rubber-magnet.com>



Dexing Magnet Tech. Co., Ltd

Enclosure Dimensions	450W×850D×565H	450W×1000D×565H	500W×820D×900H	600W×900D×1350H		1000W×1000D×2000H
Weight	145Kg	150Kg	200Kg	280Kg	320Kg	1200Kg

Add: No.86-101,RD West Jinshan, Huli Dist, Xiamen, China Zip code: 361009

Tel: 86-592-5237772

Fax: 86-592-5237901

Email:sales@magnetsource.com.cn, dexing2007@gmail.com

Home page:<http://www.magnetsource.com.cn> <http://www.magnetomachinery.com> <http://www.rubber-magnet.com>